



OWNER'S MANUAL

MPN(s): 8RBBRFL_Y, 8RBBRFL_R, 8RBBRFL_GY, 8RBBRFL_BL, 8RBBRFL_BK

SKU(s): 409015, 409017, 409014, 409016, 409013

UPC(s): 719318385258, 719318385265, 719318385296, 719318385241,
719318385203

INSTALLATION GUIDE

There are different methods one can use to install rubber flooring. This installation guide will describe how to install your rubber flooring with either double-sided tape or glue. Before installation, we recommend that you have the following:

- Glue/Double-sided tape (depending on which method of installation you choose)
- Rubber flooring
- Carpet roller
- Utility knife
- Straight edge

DOUBLE-SIDED TAPE:

1. Clean your subfloor. It needs to be free of dirt, dust, grease, and debris.
2. Make sure your subfloor is dry.
3. Lay the rubber flooring down to make sure you are okay with the look of the flooring.
4. Use the utility knife and straight edge if you get to the wall and need to cut away excess rubber flooring.
5. Apply double-sided tape to the bottom/perimeter of the rubber flooring. Remove the release paper. Apply pressure when laying the rubber flooring.
6. After the adhesive has set for an hour, use a carpet roller on the rubber flooring. If you do not have a carpet roller, stomp on the rubber flooring.



GLUE:

1. Clean your subfloor. It needs to be free of dirt, dust, grease, and debris.
2. Make sure your subfloor is dry.
3. Lay the rubber flooring down to make sure you are okay with the look of the flooring.
4. Use the utility knife and straight edge if you get to the wall and need to cut away excess rubber flooring.
5. Apply double-sided tape to the bottom/perimeter of the rubber flooring. Remove the release paper. Apply pressure when laying the rubber flooring. After the adhesive has set for an hour, use a carpet roller on the rubber flooring. If you do not have a carpet roller, stomp on the rubber flooring.
6. Roll the rubber flooring to one side of the room. Apply a thin layer of glue to the section of the subfloor that will be covered by your first strip of rubber flooring. Unroll your first strip of rubber flooring and firmly press it into the glue. Repeat this step for each strip of rubber flooring until all of your pieces have been set.
7. Once the rubber flooring has been set, use a carpet roller on the rubber flooring. If you do not have a carpet roller, stomp on the rubber flooring.





This concludes the 8RBBRFL Owner's Manual.

*If applicable to your product, make sure to tighten
all nut-and-bolt combinations before use.*

Enjoy!

DISCLAIMER

This equipment must be used with care by capable and competent individuals under supervision, if necessary.

The use of any fitness equipment, including this one, involves the potential risk of injury. You accept and assume full responsibility for any and all injuries, damages (both economic and non-economic), and losses of any type, which may occur, and you fully and forever release and discharge Titan, its insurers, employees, officers, directors, associates, and agents from any and all claims, demands, damages, rights of action, or causes of action, present or future, whether the same be known or unknown, anticipated, or unanticipated, resulting from or arising out of the use of said equipment.

TITAN MAKES NO WARRANTY WHATSOEVER WITH RESPECT TO THE EQUIPMENT, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE. BUYER ASSUMES ALL LIABILITY IN USE OF THE EQUIPMENT.

NEED HELP?

CONTACT US FIRST.

1 (800) 605-8241

info@titandistributorsinc.com / www.titan.fitness

Business Hours: Monday–Friday • 8:00 a.m.–5:00 p.m. (CT)

